LABDEX

Standard Analytical Balance LX100ABL

Email: info@labdex.com **website:** www.labdex.com

Description

It is a portable standard high speed analytical balance. Built-in magnetic sensor for faster weighing with stability. The panel features two/five operational buttons with a slide glass windscreen for easy operation and an automated external calibration Equipped with load sensor provides accuracy in weighing.

Specifications

Weighing capacity	110 g
Minimum weighing	0.004 g
Resolution	0.001 g
Stable time	≤ 3 S
Display	LED (Green) / LCD (white back light with black font)
Pan size	Φ 90 mm
Operation temp	15-35 °C
Repeat ability	±0.002 g
Liner	± 0.003 g
Draft shield size	240 x 190 x 265 mm
Calibration	External
Cal. weight	100 g
Interface	RS232
Packing size	475 x 315 x 485 mm
Gross weight	8 kg

Features

- Two or Five operational button panel
- Load cell sensor
- Sliding glass windscreen
- Green LED display
- Can be connected to external printer

- Cast aluminum outer covering
- RS232 / RS485 interfaces provides speedy communication with computers and printers

Applications

- Used for sample/standard preparation, formulation, differential weighing, density determination, interval weighing and pipette routine testing.

Optional Accessories

- RS232C & RS485
- Printer

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com